

Camera System Accessories

Supporting today's connected jobsite

PORTABLE SOLAR TRAILER

The Sensera Portable Solar Trailer provides an all-in-one lightweight mast and trailer system for quickly deploying cameras on any jobsite. The mast system supports the mounting of up to 3 complete Sensera camera systems to provide up to 180 degree coverage. The mast can be raised by one person with the built-in winch system and allows the cameras to be placed at up to 25' in height to provide ideal viewing of the site. The trailer connects to a standard trailer hitch allowing for easy portability and relocation.

- Mast height 25"
- 4 laterally extendable outriggers for stability in high winds
- 2,000 LB axle and 500 LB leaf spring rating
- 14.5" Wheel with 5 lug pattern, standard 2" ball coupler

TRAILER SPECIFICATIONS

Shipping weight	approximately 800 LBS
Dimensions	69" x 96" x 90"
Towing Configuration	Height 9' - 4.5" Width - 69" Length w/o tongue - 43" Length with tongue - 96"

CAMERA COMPATIBILITY

Supports mounting 1 - 3 Sensera cameras (models MC26, MC78, MC88, SiteWatch-PRO2 in any combination) - sold separately.

XL-models require additional cable harness and solar panels must be mast-mounted separately.



INSTALLATION STEPS

- Unhitch trailer at desired location and orientation
- Deploy outriggers and level
- Mount camera(s) on the mast
- Mount solar panels on mount arm
- Connect solar panel pigtail(s) to in-mast cable
- Connect in-mast cables to camera(s)
- Crank up mast

ORDERING INFORMATION

- AK-TI-001 Portable Solar Surveillance Trailer
- AK-TI-002 Trailer Camera Mounting Kit

NON-PENETRATING ROOF MOUNT KIT

Fixed Position & Security Cameras



SPECIFICATIONS

Base Width	35" x 35"
Pole Dimensions	2.25" diameter, 60" tall
Camera Height	<60" above mounting surface
Panel Height	<45" above mounting surface
Wind Rating	Up to 70 MPH Winds

- Minimum 200 LBS of weight evenly distributed across base
- 6+ concrete blocks weighing more than 35 LBS each is recommended (not included)

ORDERING INFORMATION

- AK-R1-001 Roof Mount Kit - MC & SWP

NON-PENETRATING ROOF MOUNT KIT

PTZ Cameras & XL Models



SPECIFICATIONS

Base Width	35" x 35"
Pole Dimensions	2.25" diameter, 60" tall
Camera Height	<60" above mounting surface
Panel Height	<45" above mounting surface
Wind Rating	Up to 70 MPH Winds

- Minimum 200 LBS of weight evenly distributed across base
- 6+ concrete blocks weighing more than 35 LBS each is recommended (not included)

ORDERING INFORMATION

- AK-R2-001 Roof Mount Kit - PTZ & XL Models

Camera System Accessories

Supporting today's connected jobsite



20' PORTABLE TELESCOPING CAMERA POLE



This 20' aluminum camera pole is the perfect mounting solution for all Sensera Systems cameras, including the MC26, MC78, MC88, and SiteWatch-Pro2. Easily install and relocate your cameras at the best location for flexible, semi-permanent progress monitoring, collaboration, safety and security applications. The pole is reusable and can be taken from site to site - just lower and remove the pole, purchase a new installation sleeve and reinstall.

ORDERING INFORMATION

- AK-PI-001** Pole Kit
- AC-PI-002** Pole Sleeve, Stop Bolt, Cap

SPECIFICATIONS

Pole Height	Telescoping pole maximum 20' length (exposed height)
Overall Length	21.5'
Base Wall Thickness	.80
Shipping Weight	Diameter 3", Top diameter 1.75"
Shipping Weight	20 LBS
Material	Maintenance-free high strength 6061 T6 anodized 0.125" aluminum
Telescoping Mechanism	Interlocking sleeves - increased bearing surface to reduce wobble between sections
Wind Rating	Up to 70 MPH gusts (single camera system)

Note: Multiple cameras not recommended and may reduce wind load capacity

SOLAR CAMERA CARRYING CASE



Strong and reliable, this case includes a custom die-cut foam insert to fit your Sensera camera system perfectly. Protects against

impacts, drops, dings, and dust. Great for storing and protecting your camera, solar panel, mounts and optional illuminator.

FEATURES

- Waterproof and dust tight
- Cushioned handles for comfortable lifting & carrying
- Wheels for easy transport
- Latches can be retrofitted with TSA accepted key locking latches
- Dimensions (inches): 49.66L x 21.50W x 8.87H
- Weight: 24.2 LBS (not including camera kit)
- Unconditional Lifetime Warranty

ORDERING INFORMATION

- AC-CI-001** Solar Camera Carrying Case

TRIPOD MOUNTING KIT (INDOOR)

SPECIFICATIONS

Height	37" x 60" (adjustable)
Weight	15 LBS

- No assembly required
- Collapse to compact size
- Secure tripod kit with cement blocks or sandbags

ORDERING INFORMATION

- AK-XI-001** Tripod Mounting Kit for MC Series Cameras
- AK-XI-002** Tripod Mounting Kit for SiteWatch PRO2 Cameras



SPECIFICATIONS SUBJECT TO CHANGE
Images are for illustration purposes only

Made in the USA